nVent | LENTON

We connect and protect

P13 Position Coupler, Plain, European Design, 25 mm, #8, 25M

CATALOG NUMBER

EL25P13EE



The European Design Version (Suffix EE) is currently being phased out. All future projects should be designed with the Worldwide Design Version (Suffixes N and LN). This change is being done in order to simplify our product offering and eliminate redundant designs. Please contact Customer Care or your local Sales Engineer/Manager if you require more information on this transition.

CERTIFICATIONS

AFCAB DISPOSITIFS DE RABOUTAGE OU D'ANCRAGE D'ARMATURES DU BÉTON

KOMO®

ERICO EUROPE B.V. Tilburg Niederlande Z-1.5-200

FEATURES

- Designed to splice the same diameter bars
- Designed to splice two curved, bent or straight bars, when neither bar can be rotated and where the ongoing bar is NOT free to move in its axial direction
- Adjustability in the female end of the coupler allows the coupler to extend out to meet the taper-threaded reinforcing bar

PRODUCT ATTRIBUTES

- Article Number: 150250
- Material: Steel
- Finish: Plain
- Design Version: European (Specialty Materials)
- Coupler Adjustment: Standard
- Rebar Size, Metric: 25 mm
- Rebar Size, US: #8

Rebar Size, Canada: 25M
Diameter (Ø): 41 mm
Length 1 (L1): 195 mm
Length 2 (L2): 255 mm
Bar Depth (BD): 41mm
Bar Gap 1 (BG1): 113mm
Bar Gap 2 (BG2): 173mm
Coupler Body (CB): 127mm
Designed to Meet: AASHTO;ABNT NBR 8548:1984;ACI 318 Type 1 (125% Specified Yield);ACI 318 Type 2 (Specified Tensile);ACI 349;ACI 359;AS3600
Unit Weight: 1.31 kg
Package Quantity: 10

ADDITIONAL PRODUCT DETAILS

Bar dimensions and weights listed may vary by region. Coupler sizes not shown may be available by special order. Contact your nVent LENTON representative for more information.

Suffix "EE" has been added to some part numbers to clarify design version among regions.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.