

# Telescoping Plumbing Bracket



## CERTIFICATIONS



## FEATURES

Notched and marked for easy identification and bending

Adjustable for non-standard stud spacing

Interlocking tab prevents accidental disassembly

Can be mounted at multiple depths to face or inside of stud

Additional pilot holes in bracket allow for easy attachment utilizing multiple standard solutions

Increased rigidity for heavier-duty plumbing applications

Requires only a screw gun to install

## SPECIFICATIONS

Table 1/1

Catalog Number	Material	Finish	Stud Spacing
TPB1624	Steel	Pregalvanized	400 - 635 mm

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause

product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical  
Support

**Europe**

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

**Europe**

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

**APAC**

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**

