

Cable to Cable, SS, 350 kcmil Concentric, 17.3 mm Conductor 1 OD, 4/0 Concentric, 13.4 mm Conductor 2 OD


Data Solutions

CATALOG NUMBER

6

6


SSC3D2Q



(Ve t ERICO Cadwe d grap te ds are des g ed a d e g eered fr t usa ds f c ect sty es a d c duct r c b at s.

+ + +
+ + +

CERTIFICATIONS



6

6 6

6

FEATURES

Fr s a per a e t, w res sta ce c ect

6

(Pr v des a ecu ar b d

(Ve t ERICO Cadwe d Ex t er c C ect s are rated w t t e sa e curre t capac ty as t e c duct r

((P rtab e sta at equ p (e t w t exter a s urce f p wer requ red

l (sta ers ca be eas y tra pd t a% (Ve t ERICO Cadwe d Ex t er c C ect s

C ect s ca be v sua y spected

+ + + + + + +
+ + + + + + +
+ + + + + + +

PRODUCT ATTRIBUTES

(M d Fa y: SS M d Fa y

C (duct r 1: 350 % C ce tr c

C duct r 1 Outer Dia eter, N a: 17.3

C duct r 2: 4/0 C ce tr c

C duct r 2 Outer Dia eter, N a: 13.41

(M d Sp t: Vert ca

Sp t Cruc b e: N + +

Wear P ates: N

M d O y: N + +

(We d g Mater a: 115 (r 115PLUSF20, S d Separate y

Ha d e C a p: L160, S d Separate y

Pr ce Key: C

Ease f Use: Preferred 6 6 6 6
+ + + +

ADDITIONAL PRODUCT DETAILS

F r app cat s suc a s c (puter r (, tu (e r t er w-ve t at ar a s, spec fy a s %e ss (Ve t ERICO Cadwe d Ex d. Add a XL pref x t e sta dard d part u ber w e (r der g (f r exa p e, a TAC2Q2Q bec es (XL TAC2Q2Q). S ar y, (Ve t (ERICO Cadwe d Ex (We d g ater a s a s des g ated by t e XL pref x (f r exa p e, 150 bec es XL150).

A gap between c duct rs ay (be requ red. See d tag f r re f r at .

+ + + + +

XX-X-XX-XX-L-M-W		
(XX	M d Fa y	
X	Pr ce Key	6 6 + + +
XX	C duct r C de 1	
XX	C duct r C de 2	6
(L*	Sp t Cruc b e	C (uc b e s e c t s sp t ds des g ed w t r z ta (pe g f r eas er c ea g
(M*	M d O y	
(W*	Wear P ates	(Reduce ec a (ca abra s f ds at cab e e try p ts

*E pty f + e + + + + + + + + +

+ + +

+

