

# CableRack

## Data Solutions



CableRack is used for ladder or basket tray mounting and securing 19-inch rack equipment for Data centers, Telecommunication rooms and other locations. The fixed, open frame rack allows suspending 19-inch rack equipment from Ladder Rack or Basket Tray. The rack has universal tapped holes per industry standards to accommodate typical applications. These open frame racks are ideal for high-density cabling applications which require above-the-cabinet mounting of equipment, and provide maximum access to cables and equipment. CableRack is ideal for Data Center applications, expanding equipment to above-the-cabinet while providing increased equipment and cable densities.

### INDUSTRY STANDARDS

---

UL 2416 Listed; File Number E230874

Rated to 60 lbs. with a 4X safety factor

### FEATURES

---

Designed to accommodate all standard 19-inch rack equipment

Easy, single-tool assembly reduces installation time and cost

Preassembled for fast, time-saving installation

Securely mounts to either Cable Runway (Ladder Rack) or Basket Tray

UL double lug ground holes provide easy adherence to local bonding and grounding codes

Cable tie down points, sized for up to 1-inch Velcro® straps, provided in horizontal and vertical positions in multiple locations

Parallel or perpendicular mounting to cable pathway

Multi-point mounting provisions address various application needs

Open design provides for maximum access to cables and equipment

Smart packaging with hand-carrying holes allow for easy transportation

### SPECIFICATIONS

---

Table 1/2

Catalog Number	Article Number	Material	Finish	Color	Color Code	Thickness
E19T6U	26176	Mild Steel	Powder Coated	Jet Black	RAL 9005	1.9mm

Table 2/2

Catalog Number	Article Number	Rack Units
E19T6U	26176	6U

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**