

Compression Straight Lug, Square Mount



CERTIFICATIONS



FEATURES

Attaches stranded cable to receptors or hubs

SPECIFICATIONS

Material: Aluminum
Finish: Tinned

Table 1/1

Catalog Number	Conductor Size	Hole Size (HS)	Length (L)	Width (W)
ECLA2S14	#2 Stranded	6.5 mm	63.5mm	18 mm
ECLA250S38	250 kcmil Stranded	10.5 mm	72.9mm	32 mm
ECLA250S12	250 kcmil Stranded	13 mm	72.9mm	32 mm
ECLA250S12BX	250 kcmil Stranded	13 mm	72.9mm	32 mm
ECLA250S58	250 kcmil Stranded	17 mm	72.9mm	32 mm
ECLA250S58BX	250 kcmil Stranded	18 mm	72.9mm	32 mm

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE