


Copper Shim



FEATURES

Wrapped around the cable until the diameter is about the same as the cable opening in the mold


SPECIFICATIONS

Material: Copper

Table 1/1

Catalog Number	Article Number	Length (L)	Width (W)	Thickness (T)
B140K		114.3mm	38.1 mm	0.33 mm
B141C		63.5mm	76.2 mm	0.33 mm
B141A		38.1mm	76.2 mm	0.33 mm
B140A		38.1mm	76.2 mm	0.33 mm
B140L		139.7mm	38.1 mm	0.33 mm
B140B		63.5mm	76.2 mm	0.33 mm
B140N	165610	76.2mm	38.1 mm	0.33 mm

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

⚠ **WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE