

## Cable Clamps, CAC



The cable clamps secures cables into position and relieves any external strains which in turn helps prevent equipment damage.

### FEATURES

---

Description: To secure incoming cables onto the fixing bars CAB and CABP. Holds the cable in position and supports the weight.

Material: Zinc plated steel.

Pack quantity: 25 clamps.

Mounting requirements: Add CAB/CABP to mount the cable clamps CAC.

## SPECIFICATIONS

**Thickness:** 2mm  
**Material:** Mild Steel  
**Finish:** Zinc Plated

Table 1/1

Catalog Number	Article Number	Height	Width	Depth	Enclosure Material	Product Family
CAC0612	CAC0612	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC1014	CAC1014	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC1216	CAC1216	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC1418	CAC1418	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC1822	CAC1822	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC3842	CAC3842	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC3438	CAC3438	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC2226	CAC2226	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC2630	CAC2630	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC4246	CAC4246	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC5864	CAC5864	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing
CAC3034	CAC3034	64mm	25mm	19mm	Mild Steel, Stainless Steel	Free-Standing

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**