

Joint Bond Mold Only, Power

Data Solutions



FEATURES

Replacement mold designed for the installation of jumper bonds to the head of the rail

Connection is made within the confines of the splice plate

SPECIFICATIONS

Bond Terminal Style: C

Material: Graphite

Table 1/1

| Catalog Number | Article Number | Rail Type | Conductor Size | Conductor Outer Diameter, Nominal | Orientation |
|----------------|----------------|---------------------------------|-----------------------------|-----------------------------------|-------------|
| MRR50G | 547910 | UIC54, UIC60 | 50 mm ² Stranded | 9.27mm | Right Hand |
| MRR50D | 547900 | UIC54, UIC60 | 50 mm ² Stranded | 9.27mm | Left Hand |
| PBCS6CWPRHM | | 85 lb to 141 lb T-Rail Sections | 3/0 Composite | 14.53mm | Right Hand |
| PBCS6CWPLHM | | 85 lb to 141 lb T-Rail Sections | 3/0 Composite | 14.53mm | Left Hand |
| PBC2WLHM | | 85 lb to 141 lb T-Rail Sections | 250 kcmil Ropelay | 19.05mm | Left Hand |
| PBC2WRHM | | 85 lb to 141 lb T-Rail Sections | 250 kcmil Ropelay | 19.05mm | Right Hand |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE