

Nipple Feed-Through



Feed-Through Nipples are used between adjacent wireway sections or fittings for adjusting wireway length. Connects to other wireway sections and fittings and protects wires and cables against dust in a broad range of industrial applications.

INDUSTRY STANDARDS

Certified by Canadian Standards Association.

FEATURES

Feed-Through Nipples are used between adjacent wireway sections or fittings for adjusting wireway length

Connects to other wireway sections and fittings and protects wires and cables against dust in a broad range of industrial applications

SPECIFICATIONS

Color Code: ANSI 61
Color: Gray
Material: Mild Steel
Finish: Powder Coated

Table 1/1

| Catalog Number | Article Number | Type | Height | Width | Depth | Thickness |
|----------------|----------------|--------|--------|-------|-------|-----------|
| F44WN1 | 14850 | Nipple | 102mm | 102mm | 25mm | 1.9mm |
| F22WN1 | 14810 | Nipple | 64mm | 64mm | 25mm | 1.9mm |
| F88WN1 | 14930 | Nipple | 203mm | 203mm | 25mm | 1.9mm |
| F66WN1 | 14890 | Nipple | 152mm | 152mm | 25mm | 1.9mm |
| F88WN6 | 14960 | Nipple | 203mm | 203mm | 152mm | 1.9mm |
| F22WN2 | 14820 | Nipple | 64mm | 64mm | 51mm | 1.9mm |
| F22WN3 | 14830 | Nipple | 64mm | 64mm | 76mm | 1.9mm |
| F22WN6 | 14840 | Nipple | 64mm | 64mm | 152mm | 1.9mm |
| F44WN2 | 14860 | Nipple | 102mm | 102mm | 51mm | 1.9mm |
| F44WN3 | 14870 | Nipple | 102mm | 102mm | 76mm | 1.9mm |
| F44WN6 | 14880 | Nipple | 102mm | 102mm | 152mm | 1.9mm |
| F66WN2 | 14900 | Nipple | 152mm | 152mm | 51mm | 1.9mm |
| F66WN3 | 14910 | Nipple | 152mm | 152mm | 76mm | 1.9mm |
| F66WN6 | 14920 | Nipple | 152mm | 152mm | 152mm | 1.9mm |
| F88WN2 | 14940 | Nipple | 203mm | 203mm | 51mm | 1.9mm |
| F88WN3 | 14950 | Nipple | 203mm | 203mm | 76mm | 1.9mm |

ADDITIONAL PRODUCT DETAILS

All dimensions are to outside surfaces. Allow .12 in. (3 mm) additional for gasket at joints.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE