

nVent CADDY All-in-One Between-Stud Bracket



CERTIFICATIONS



BABA



FEATURES

Versatile bracket for mounting nVent CADDY All-in-One box assemblies

Provides excellent rigidity and reduces issues at trim out

nVent CADDY All-in-One box assemblies simply slide and lock in to place with provided screws

Perfect for jobs when specifications require precise box location

24" stud spacing requires use of three mounting screws.

SPECIFICATIONS

Table 1/1

Catalog Number	Material	Finish	Stud Spacing	A	B
A1B1624	Steel	Pregalvanized	16" - 24"	5 3/8"	4 1/8"

ADDITIONAL PRODUCT DETAILS

Use only with nVent CADDY All-in-One box assemblies.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

