

Cable to Cable, Rail

Data Solutions



nVent ERICO Cadweld applications for railway properties utilize the nVent ERICO Cadweld Plus F80 and the nVent ERICO Cadweld F80 welding material alloys. nVent ERICO Cadweld exothermically welded connections are engineered to provide a permanent, molecular bond that will not loosen or corrode, enabling connection of dissimilar materials. The connections are designed to perform for the life of the conductor and/or installation. The nVent ERICO Cadweld connection has a current carrying capacity equal to or greater than that of the conductor and will withstand repeated fault currents without failing during operation. Once completed, installers can clearly ensure quality by visually inspecting the new connection.

FEATURES

Forms a permanent, low resistance connection

Provides a molecular bond

nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor

Portable installation equipment with no external source of power required

Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections

Connections can be visually inspected

SPECIFICATIONS

Table 1/5

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB10PA1G1G	PA Mold Family	#6 Solid	0.16in	#6 Solid	0.16in
SB10SS1H1G	SS Mold Family	#6 Concentric	0.18in	#6 Solid	0.16in
SB02SS6	SS Mold Family	#6 Solid	0.16in	#6 Solid	0.16in
PB10SS2Q1H	SS Mold Family	4/0 Concentric	0.53in	#6 Concentric	0.18in
PB20TA2Q1H	TA Mold Family	4/0 Concentric	0.53in	#6 Concentric	0.18in
PB20TA2G1H	TA Mold Family	2/0 Concentric	0.42in	#6 Concentric	0.18in

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB10PC2C1H	PC Mold Family	1/0 Concentric	0.37in	#6 Concentric	0.18in
SB10SS1V3	SS Mold Family	#2 Concentric	0.29in	3/16 Signal	0.1875in
PB10SS2Q1L	SS Mold Family	4/0 Concentric	0.53in	#4 Concentric	0.23in
PB20TA2V1L	TA Mold Family	250 kcmil Concentric	0.57in	#4 Concentric	0.23in
PB20TA1L2V	TA Mold Family	#4 Concentric	0.23in	250 kcmil Concentric	0.57in
PB10SS1T	SS Mold Family	#2 Solid	0.26in	#2 Solid	0.26in
PB20TA2Q1V	TA Mold Family	4/0 Concentric	0.53in	#2 Concentric	0.29in
SB10SS1V	SS Mold Family	#2 Concentric	0.29in	#2 Concentric	0.29in
PB10SS1Y	SS Mold Family	#1 Concentric	0.33in	#1 Concentric	0.33in
PB20PAY3Y3	PA Mold Family	50 mm ² Concentric	0.35in	50 mm ² Concentric	0.35in
PB20TAT2Y3	TA Mold Family	10.0 mm Ground Wire	0.39in	50 mm ² Concentric	0.35in
PB20TA2C2C	TA Mold Family	1/0 Concentric	0.37in	1/0 Concentric	0.37in
PB10SS2C	SS Mold Family	1/0 Concentric	0.37in	1/0 Concentric	0.37in
PB20PP2CPS	PP Mold Family	1/0 Concentric	0.37in	B154A Plug	0.5in

Table 2/5

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB10SS2Q2C	SS Mold Family	4/0 Concentric	0.53in	1/0 Concentric	0.37in
PB20PP2G2PS	PP Mold Family	2/0 Concentric	0.42in	B154A Plug	0.5in
PB10SS2Q2G	SS Mold Family	4/0 Concentric	0.53in	2/0 Concentric	0.42in
PB10SS2G	SS Mold Family	2/0 Concentric	0.42in	2/0 Concentric	0.42in
PB20TA2Q2G	TA Mold Family	4/0 Concentric	0.53in	2/0 Concentric	0.42in
PB99XB2Q2G	XB Mold Family	4/0 Concentric	0.53in	2/0 Concentric	0.42in
PB20PG2G2G	PG Mold Family	2/0 Concentric	0.42in	2/0 Concentric	0.42in
PB20TA2G2G	TA Mold Family	2/0 Concentric	0.42in	2/0 Concentric	0.42in
PB10PT2G2G	PT Mold Family	2/0 Concentric	0.42in	2/0 Concentric	0.42in
PB10SS2J	SS Mold Family	2/0 Ropelay	0.48in	2/0 Ropelay	0.48in
PB20PPS6PS	PP Mold Family	3/0 Composite	0.57in	B154A Plug	0.5in
PB20TAS5S5	TA Mold Family	2/0 Composite	0.53in	2/0 Composite	0.53in
PB10SS2Q	SS Mold Family	4/0 Concentric	0.53in	4/0 Concentric	0.53in
PB13SV2Q	SV Mold Family	4/0 Concentric	0.53in	4/0 Concentric	0.53in

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB10SS2S2Q	SS Mold Family	4/0 Ropelay	0.61in	4/0 Concentric	0.53in
PB99XB2Q2Q	XB Mold Family	4/0 Concentric	0.53in	4/0 Concentric	0.53in
PB10SS2V2Q	SS Mold Family	250 kcmil Concentric	0.57in	4/0 Concentric	0.53in
PB20TA2Q4R	TA Mold Family	4/0 Concentric	0.53in	1100/#24 Ropelay	0.88in
PB20TA2Q2Q	TA Mold Family	4/0 Concentric	0.53in	4/0 Concentric	0.53in
PB10PC2Q2S	PC Mold Family	4/0 Concentric	0.53in	4/0 Ropelay	0.61in

Table 3/5

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB10PTS6S6	PT Mold Family	3/0 Composite	0.57in	3/0 Composite	0.57in
PB20TA2V2V	TA Mold Family	250 kcmil Concentric	0.57in	250 kcmil Concentric	0.57in
PB99XB2V2VM	XB Mold Family	250 kcmil Concentric	0.57in	250 kcmil Concentric	0.57in
PB10SSS6	SS Mold Family	3/0 Composite	0.57in	3/0 Composite	0.57in
PB10SS2V	SS Mold Family	250 kcmil Concentric	0.57in	250 kcmil Concentric	0.57in
PB99XB2V2V	XB Mold Family	250 kcmil Concentric	0.57in	250 kcmil Concentric	0.57in
PB10SS2W2V	SS Mold Family	250 kcmil Ropelay	0.75in	250 kcmil Concentric	0.57in
PB10SS2S	SS Mold Family	4/0 Ropelay	0.61in	4/0 Ropelay	0.61in
PB10SS2W3DC	SS Mold Family	250 kcmil Ropelay	0.75in	350 kcmil Compact	0.625in
PB10SSS7	SS Mold Family	4/0 Composite	0.66in	4/0 Composite	0.66in
PB10SS3SS7	SS Mold Family	500 kcmil Ropelay	1.04in	4/0 Composite	0.66in
PB10SS4K2W	SS Mold Family	650/#24 Ropelay	0.67in	250 kcmil Ropelay	0.75in
PB10SS3Q3D	SS Mold Family	500 kcmil Concentric	0.81in	350 kcmil Concentric	0.68in
PB10SS3S3D	SS Mold Family	500 kcmil Ropelay	1.04in	350 kcmil Concentric	0.68in
PB10SS3D	SS Mold Family	350 kcmil Concentric	0.68in	350 kcmil Concentric	0.68in
PB20TA3QC3QC	TA Mold Family	500 kcmil Compact	0.73in	500 kcmil Compact	0.73in

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB10SS3S3QC	SS Mold Family	500 kcmil Ropelay	1.04in	500 kcmil Compact	0.73in
PB10SS3QC3S	SS Mold Family	500 kcmil Compact	0.73in	500 kcmil Ropelay	1.04in
PB50PC5A2W	PC Mold Family	1000 kcmil Ropelay	1.33in	250 kcmil Ropelay	0.75in
PB10SS2W	SS Mold Family	250 kcmil Ropelay	0.75in	250 kcmil Ropelay	0.75in

Table 4/5

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB10SS3S4M	SS Mold Family	500 kcmil Ropelay	1.04in	775 kcmil/#24 Ropelay	0.75in
PB50SS5A2W	SS Mold Family	1000 kcmil Ropelay	1.33in	250 kcmil Ropelay	0.75in
PB50PC3S2W	PC Mold Family	500 kcmil Ropelay	1.04in	250 kcmil Ropelay	0.75in
PB20TA2W3S	TA Mold Family	250 kcmil Ropelay	0.75in	500 kcmil Ropelay	1.04in
PB10SS2W3S	SS Mold Family	250 kcmil Ropelay	0.75in	500 kcmil Ropelay	1.04in
PB10SS3B3S	SS Mold Family	300 kcmil Ropelay	0.8in	500 kcmil Ropelay	1.04in
PB10SS3Q	SS Mold Family	500 kcmil Concentric	0.81in	500 kcmil Concentric	0.81in
PB10SS3S3Q	SS Mold Family	500 kcmil Ropelay	1.04in	500 kcmil Concentric	0.81in
PB63TA6H3Q	TA Mold Family	2000 kcmil Concentric	1.61in	500 kcmil Concentric	0.81in
PB60TA3Q4Y	TA Mold Family	500 kcmil Concentric	0.81in	1000 kcmil Concentric	1.15in
PB20TA3Q3Q	TA Mold Family	500 kcmil Concentric	0.81in	500 kcmil Concentric	0.81in
PB80PG5T3Q	PG Mold Family	1500 kcmil Concentric	1.41in	500 kcmil Concentric	0.81in
PB60TA4Y3Q	TA Mold Family	1000 kcmil Concentric	1.15in	500 kcmil Concentric	0.81in
PB10SS4R	SS Mold Family	1100/#24 Ropelay	0.88in	1100/#24 Ropelay	0.88in
PB10SS3S3F	SS Mold Family	500 kcmil Ropelay	1.04in	350 kcmil Ropelay	0.88in
PB20TA4R4R	TA Mold Family	1100/#24 Ropelay	0.88in	1100/#24 Ropelay	0.88in
PB31TA4T4T	TA Mold Family	1325/#24 Ropelay	0.98in	1325/#24 Ropelay	0.98in
PB50SS4L4T	SS Mold Family	750 kcmil Concentric	1in	1325/#24 Ropelay	0.98in

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB10SS3S4T	SS Mold Family	500 kcmil Ropelay	1.04in	1325/#24 Ropelay	0.98in
PB80PA5T4L	PA Mold Family	1500 kcmil Concentric	1.41in	750 kcmil Concentric	1in

Table 5/5

Catalog Number	Mold Family	Conductor 1	Conductor 1 Outer Diameter, Nominal	Conductor 2	Conductor 2 Outer Diameter, Nominal
PB50SS4L3S	SS Mold Family	750 kcmil Concentric	1in	500 kcmil Ropelay	1.04in
PB10SS4L	SS Mold Family	750 kcmil Concentric	1in	750 kcmil Concentric	1in
PB20TA3S3S	TA Mold Family	500 kcmil Ropelay	1.04in	500 kcmil Ropelay	1.04in
PB50PC3S5A	PC Mold Family	500 kcmil Ropelay	1.04in	1000 kcmil Ropelay	1.33in
PB60TA4N3S	TA Mold Family	750 kcmil Ropelay	1.16in	500 kcmil Ropelay	1.04in
PB50SS3S4N	SS Mold Family	500 kcmil Ropelay	1.04in	750 kcmil Ropelay	1.16in
PB10SS3S	SS Mold Family	500 kcmil Ropelay	1.04in	500 kcmil Ropelay	1.04in
PB10SS3S4X	SS Mold Family	500 kcmil Ropelay	1.04in	1600/#24 Ropelay	1.07in
PB50SS3S4Y	SS Mold Family	500 kcmil Ropelay	1.04in	1000 kcmil Concentric	1.15in
PB50SS3S5A	SS Mold Family	500 kcmil Ropelay	1.04in	1000 kcmil Ropelay	1.33in
PB60TA4X4X	TA Mold Family	1600/#24 Ropelay	1.07in	1600/#24 Ropelay	1.07in
PB50SS4Y	SS Mold Family	1000 kcmil Concentric	1.15in	1000 kcmil Concentric	1.15in
PB50SS4N	SS Mold Family	750 kcmil Ropelay	1.16in	750 kcmil Ropelay	1.16in
PB50SS5A	SS Mold Family	1000 kcmil Ropelay	1.33in	1000 kcmil Ropelay	1.33in
PB50PC5A5A	PC Mold Family	1000 kcmil Ropelay	1.33in	1000 kcmil Ropelay	1.33in
PB53SS6H	SS Mold Family	2000 kcmil Concentric	1.61in	2000 kcmil Concentric	1.61in

ADDITIONAL PRODUCT DETAILS

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless nVent ERICO Cadweld Exolon mold. Add an XL prefix to the standard mold part number when ordering (for example, a PB10GR162G becomes XLPB10GR162G). Similarly, nVent ERICO Cadweld Exolon welding material is also designated by the XL prefix (for example, PB90 becomes XLPB90).

A gap between conductors may be required. See mold tag for more information.

XXXX-XX-XX-XX-L-M-W		
XXXX	Price Key	
XX	Mold Family	
XX	Conductor Code 1	
XX	Conductor Code 2	
L*	Split Crucible	Crucible section is split on molds designed with horizontal opening for easier cleaning
M*	Mold Only	
W*	Wear Plates	Reduce mechanical abrasion of molds at cable entry points

* Empty if none

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE