

Conductor Sleeve

Data Solutions



FEATURES

Used to adapt a limited range of smaller size cables to a larger size nVent ERICO Cadweld Mold

Provides strength and stability on finely-stranded copper conductors

SPECIFICATIONS

Material: Copper

Table 1/2


Catalog Number	Finish	Type	Length (L)	Thickness (T)	Diameter (Ø)
S429F2J16	Tinned	Flared	1in	0.02in	0.48in
S429F2N16	Tinned	Flared	1in	0.02in	0.54in
S07F	Tinned	Flared	1in	0.03in	0.67in
S05F	Tinned	Flared	1in	0.03in	0.39in
B1331K	Tinned	Straight	1in	0.03in	0.14in
S03F	Tinned	Flared	1in	0.03in	0.46in
S17F	Tinned	Flared	1in	0.03in	0.34in
B112	Tinned	Straight	1.06in	0.03in	0.21in
S02F	Tinned	Flared	1in	0.03in	0.61in
PBS24F	Tinned	Flared	1.5in	0.03in	0.8in

Catalog Number	Finish	Type	Length (L)	Thickness (T)	Diameter (Ø)
S429F3S20	Tinned	Flared	1.25in	0.03in	0.93in
H106F		Flared	1.02in	0.04in	0.59in
H102		Straight	0.98in	0.04in	0.17in
H101		Straight	1.02in	0.04in	0.24in
H113F		Flared	1.02in	0.04in	0.31in
H106AF		Flared	1.38in	0.04in	0.59in
H105		Straight	0.93in	0.04in	0.12in
H102F		Flared	1.02in	0.04in	0.17in
H117		Straight	0.98in	0.04in	0.28in
H103		Straight	0.98in	0.05in	0.21in

Table 2/2

Catalog Number	Finish	Type	Length (L)	Thickness (T)	Diameter (Ø)
180380	Tinned	Flared	0.98in	0.09in	0.21in

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE