

L-Box Type 1, 24.00x24.00x12.00, Lt Gray, Steel

Data Solutions

CATALOG NUMBER

DBL242412G



The low-profile, vertically-oriented L-Box wall-mount cabinet is extremely versatile and can be used in public settings to mount, store and protect network equipment, patch panels and connections. The hinged, L-shaped door provides full access on two sides to installed equipment while fixed rack angles accommodate varying equipment sizes.

INDUSTRY STANDARDS

UL 2416 Listed; File No. E230874

cUL Listed per CSA C22.2 No. 182.4; File No. E230874

Ventilation complies with UL 60950

Designed in accordance with BICSI TDMM Tenth edition, Chapter 7, Telecommunication Enclosures (TE)

EIA 310-D

IEC 60529, IP30

NEMA Type 1

FEATURES

Spring-loaded, self-retained hinge pins allow door removal

120-degree door opening for maximum equipment access

Quarter-turn latches with key lock

One set of fixed rack angles is included on 24- and 36-inch (610- and 914-mm) tall models and two on 48-inch (1219-mm) tall models

Rack angles on 36-inch (914-mm) models can be positioned either at the top or the bottom of the cabinet

36- and 48-inch (914- and 1219-mm) tall models have space for patch panel or shelf brackets

Knockouts for 4-inch (102-mm) fan on top and bottom of cabinet

Wiring knockouts (7/8 inch, 1-3/8 inch, and 3 inch) on top and bottom of cabinet & two 3-inch cable entry knockouts on back

Multiple cable tie-down points on back of cabinet

Keyhole mounting slots spaced 16.00 inch (406 mm) on center for easy cabinet mounting

PRODUCT ATTRIBUTES

Article Number: 14373

Height: 24in

Width: 24in

Depth: 12.34in

Material: Mild Steel

Finish: Powder Coated

Color: Light Gray

Color Code: RAL 7035

Thickness: 14ga

Rack Units: 6U

Weight: 60lb

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE