

Beam Clamp for Solid Round Conductor



FEATURES

Clamp for attaching solid round conductor such as nVent ERICO Cu-Bond Round Conductor to flat metal objects such as I-beams, angle irons and channel irons

For use with copper-bonded, copper, or stainless steel solid conductors

SPECIFICATIONS

Table 1/2

Catalog Number	Material	Width (W)	Height (H)	Depth (D)	Flange Thickness (FT)	nVent ERICO Cu-Bond Conductor
SBCS1314	Stainless Steel 316 (EN 1.4401)	2.17"	3.54"	2.76"	1/4" - 1"	CBSC13, CBSC14

Table 2/2

Catalog Number	Unit Weight	Complies With
SBCS1314	0.61 lb	IEC® 62561-4

ADDITIONAL PRODUCT DETAILS

IEC compliance is valid only for nVent ERICO Cu-Bond Conductors listed.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE