

# Cross Fitting Lay-in Hinged-Cover



Lay-in Hinged-Cover Cross Fittings are used for routing cables in four directions in wireway runs. Used when there are four branches, all open along the same side.

## INDUSTRY STANDARDS

---

Certified by Canadian Standards Association

## FEATURES

---

Lay-in Hinged-Cover Cross Fittings are used for routing cables in four directions in wireway runs

Used when there are four branches, all open along the same side

## SPECIFICATIONS

---

**Color Code:** ANSI 61  
**Finish:** Galvanized; Powder Coated  
**Color:** Gray  
**Material:** Mild Steel

Table 1/1

Catalog Number	Article Number	Type	Height	Width	Thickness
F88LC	19310	Cross Fitting	8in	8in	14ga
F66LC	18660	Cross Fitting	6in	6in	14ga
F44LC	18420	Cross Fitting	4in	4in	14ga
F126LC	18860	Cross Fitting	12in	6in	14ga
F22LC	18190	Cross Fitting	2.5in	2.5in	14ga

## ADDITIONAL PRODUCT DETAILS

---

Each sealing plate also includes one gasket and one set of screws to join sections.

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**