

# Handles Concept

Handles replace the standard slotted insert on all Concept wall-mount enclosures.



## FEATURES

---

A zinc die-cast key lock handle (CWHK) is available for applications requiring quick access and security

A padlocking handle (CWHPTO), also zinc die-cast, accommodates a padlock with up to a 5/16-in. locking bar

Each latch system can be converted from clockwise to counter-clockwise opening

Kit includes handle, sealing washer, wave washer, instruction manual and keys if handle is lockable

## SPECIFICATIONS

Table 1/1

Catalog Number	Article Number	Height	Width	Depth	Product Family	Material
CWHNL	79390	1.94in	0.79in	0.88in	Concept	Mild Steel
CWHPTO	79410	3.54in	1in	1.57in	Concept	Mild Steel
CWHK	79400	2.5in	1.02in	1.52in	Concept	Mild Steel

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**