

# Partial Height Swing Frames, SFCP



A partial height swing frame for 19" equipment that provides additional mounting space for such equipment, as well as rear access to the fitted components and equipment once opened.

## FEATURES

Description: Partial height swing frame for 19"-components allowing left or right hand opening. Can be used in wall mounted, steel enclosures, and floor standing, combinable and compact, steel enclosures. Rigid S-shaped frame profile equipped with 19" hole pattern in front and back. Zinc plated frame for direct earthing of the mounted components. Standard opening angle 125°-155°. Mounting in wall mounted, steel enclosures requires the SFBP transversal support in combination with the AVB. Mounting in floor standing steel combinable enclosures requires the SFBP transversal support.

Lock: 1 double-bit 3 mm lock.

Material: 2 mm zinc plated steel.

Pack quantity: 1 swing frame with hinges.

Mounting requirements: Mounting in wall mounted, steel enclosures requires the SFBP transversal support in combination with the AVB. Mounting in floor standing steel combinable enclosures requires the SFBP transversal support. Adjustable in depth in combination with CLPK profiles.

## SPECIFICATIONS

---

**Thickness:** 14ga  
**Material:** Mild Steel  
**Finish:** Zinc Plated

Table 1/1

Catalog Number	Article Number	Height	Width	Depth	Enclosure Material	Load Rating
SFCP066	SFCP066	23.62in	19.53in	2.36in	Mild Steel	300N
SFCP196	SFCP196	39.37in	35.28in	2.36in	Mild Steel	500N
SFCP106	SFCP106	23.62in	19.53in	2.36in	Mild Steel	500N
SFCP126	SFCP126	31.5in	27.4in	2.36in	Mild Steel	500N
SFCP246	SFCP246	47.24in	43.15in	2.36in	Mild Steel	500N
SFCP036	SFCP036	23.62in	19.53in	2.36in	Mild Steel	150N
SFCP156	SFCP156	31.5in	27.4in	2.36in	Mild Steel	500N

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**