


Ultrx Swing-Out Panel



Swing-Out Panel installs into Ultrx fiberglass enclosures. The front-mounted swing panel complements window-door units and is suited for any application requiring a display of gauges, dials or any type of control equipment monitor. Easy installation; no drilling required. Fully adjustable front to rear. Front mounting position is approximately 140mm (5.5 inch) back on 400mm enclosures. Panel, mounting hardware and instruction manual included.

CERTIFICATIONS



FEATURES

For use with Ultrx Series Products

SPECIFICATIONS

Table 1/1

Catalog Number	Article Number	Material	Finish	Color	Thickness
UU7560SP	33760	Mild Steel	Powder Coated	White	16ga
UU6050SP	34770	Mild Steel	Powder Coated	White	16ga
UU10080SP	34780	Mild Steel	Powder Coated	White	16ga
UU6060SP	33750	Mild Steel	Powder Coated	White	16ga
UU5040SP	33740	Mild Steel	Powder Coated	White	16ga

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE