



Horizontal Rail, Front, Type L-OD, Light, Without Lip, 40 HP

CATALOG NUMBER

34560-040



Combinations of horizontal rails and side panels

		Combinations of horizontal rails and side panels			
		"4" can be combined		"2" combination not recommended	
Subrack 2 U	Subrack 4 U	-	+	+	+
Subrack 2 U	Subrack 6 U	+	+	+	+
Subrack 2 U	Subrack 8 U	+	+	-	-
Subrack 2 U	Subrack 10 U	+	+	-	-
Subrack 2 U	Subrack 12 U	+	+	-	-
Subrack 2 U	Subrack 14 U	+	+	-	-
Subrack 2 U	Subrack 16 U	+	+	-	-
Subrack 2 U	Subrack 18 U	+	+	-	-
Subrack 2 U	Subrack 20 U	+	+	-	-
Subrack 2 U	Subrack 22 U	+	+	-	-
Subrack 2 U	Subrack 24 U	+	+	-	-
Subrack 2 U	Subrack 26 U	+	+	-	-
Subrack 2 U	Subrack 28 U	+	+	-	-
Subrack 2 U	Subrack 30 U	+	+	-	-
Subrack 2 U	Subrack 32 U	+	+	-	-
Subrack 2 U	Subrack 34 U	+	+	-	-
Subrack 2 U	Subrack 36 U	+	+	-	-
Subrack 2 U	Subrack 38 U	+	+	-	-
Subrack 2 U	Subrack 40 U	+	+	-	-

The horizontal rail without a lip enable the use of a setups such as a 6 U front panel for a subrack which is split into 2 x 3 U.

CERTIFICATIONS



FEATURES

For installation behind full-width front panel

< 28 HP not to print

Without lip (L-OD)

Aluminum extrusion, anodized finish, conductive contact surface

PRODUCT ATTRIBUTES

Rack Width: 40HP

Package Quantity: 1

Finish: Anodized

Material: Aluminum

Product Family: EuropacPRO; RatiopacPRO; RatiopacPRO AIR; CompacPRO; PropacPRO

Product Type: Horizontal Rail

Type: Light, OD

Works With: Subracks; Cases

Net Weight: 0.064kg

ADDITIONAL PRODUCT DETAILS

Please take into consideration that deliveries may be carried out in the stated SPQs (SPQ, e.g. 5 pieces, 10 pieces, 50 pieces, etc.). Differing order quantities (e.g. 2 pieces) may be changed to the next possible delivery quantity = Standard Pack Quantity.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE