

Carril horizontal, Trasero, Tipo R-ST, Resistente, Estándar, 1000 mm

NÚMERO DE CATÁLOGO

34566-501



Combinations of horizontal rails and side panels

	"A" can be combined		"B" combination not recommended	
RAILWAY A		-		
RAILWAY B		+		
RAILWAY C				-
RAILWAY D		-	-	-
RAILWAY E		-	-	-
RAILWAY F		-	-	-
RAILWAY G		-	-	-
RAILWAY H		-	-	-
RAILWAY I		-	-	-
RAILWAY J		-	-	-
RAILWAY K		-	-	-
RAILWAY L		-	-	-
RAILWAY M		-	-	-
RAILWAY N		-	-	-
RAILWAY O		-	-	-
RAILWAY P		-	-	-
RAILWAY Q		-	-	-
RAILWAY R		-	-	-
RAILWAY S		-	-	-
RAILWAY T		-	-	-
RAILWAY U		-	-	-
RAILWAY V		-	-	-
RAILWAY W		-	-	-
RAILWAY X		-	-	-
RAILWAY Y		-	-	-
RAILWAY Z		-	-	-
RAILWAY AA		-	-	-
RAILWAY AB		-	-	-
RAILWAY AC		-	-	-
RAILWAY AD		-	-	-
RAILWAY AE		-	-	-
RAILWAY AF		-	-	-
RAILWAY AG		-	-	-
RAILWAY AH		-	-	-
RAILWAY AI		-	-	-
RAILWAY AJ		-	-	-
RAILWAY AK		-	-	-
RAILWAY AL		-	-	-
RAILWAY AM		-	-	-
RAILWAY AN		-	-	-
RAILWAY AO		-	-	-
RAILWAY AP		-	-	-
RAILWAY AQ		-	-	-
RAILWAY AR		-	-	-
RAILWAY AS		-	-	-
RAILWAY AT		-	-	-
RAILWAY AU		-	-	-
RAILWAY AV		-	-	-
RAILWAY AW		-	-	-
RAILWAY AX		-	-	-
RAILWAY AY		-	-	-
RAILWAY AZ		-	-	-
RAILWAY BA		-	-	-
RAILWAY BB		-	-	-
RAILWAY BC		-	-	-

El riel horizontal, tipo robusto ST permite el montaje aislado de un backplane. El aislamiento se realiza mediante una tira de aislamiento.

CERTIFICACIONES



CARACTERÍSTICAS

Riel horizontal "robusto" tipo R-ST con fijación de 3 orificios para una mayor robustez

Extrusión de aluminio, acabado anodizado, superficie de contacto conductora, con marcas HP

Con unidades HP impresas desde 28 HP hacia arriba

ATRIBUTOS DEL PRODUCTO

Ancho del rack: 195HP

Cantidad del paquete: 1

Acabado: Anodizado

Longitud: 1000mm

Material: Aluminio

Familia de productos: EuropacPRO

Tipo de producto: Carril horizontal

Tipo: Robusto, ST

Compatible con: Subpistas

Net Weight: 0.5kg

DETALLES ADICIONALES DEL PRODUCTO

Tenga en cuenta que las entregas pueden realizarse en los SPQ indicados (SPQ, por ejemplo, 5 piezas, 10 piezas, 50 piezas, etc.). Diferentes cantidades de pedido (por ejemplo, 2 piezas) se pueden cambiar a la siguiente cantidad de entrega posible = Cantidad de paquete estándar.

ADVERTENCIA

Los productos nVent deben instalarse y usarse solo como se indica en las hojas de instrucciones y materiales de capacitación del producto nVent. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. La instalación incorrecta, el mal uso, la aplicación incorrecta u otras fallas en el seguimiento completo de las instrucciones y advertencias de nVent pueden causar el mal funcionamiento del producto, daños a la propiedad, lesiones corporales graves y la muerte y/o anular la garantía.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Nuestra poderosa cartera de marcas:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE