

Clean Tray, suoran osion liitos



Clean Tray Straight section splices are used for connecting two fittings with tabs. Available with 20-degree slope in some sizes. The Clean Tray stainless steel system is designed to protect rated cabling in applications that require frequent washdown.

FEATURES

Clean Tray Straight section splices are used for connecting two fittings with tabs

Available with 20-degree slope in some sizes

The Clean Tray stainless steel system is designed to protect rated cabling in applications that require frequent washdown

SPECIFICATIONS

Finish: Brushed #3

Material: Stainless Steel 304

Table 1/1

Catalog Number	Type	Height	Width	Depth	Thickness
CT22PSPSS	Nipple	51mm	51mm	152mm	1.27mm
CT22SPSS	Nipple	51mm	51mm	152mm	1.27mm
CTS33PSPSS	Nipple	76mm	76mm	152mm	1.27mm
CT66SPSS	Nipple	152mm	152mm	152mm	1.27mm
CTS33SPSS	Nipple	76mm	76mm	152mm	1.27mm
CTS46PSPSS	Nipple	102mm	152mm	152mm	1.27mm
CT33PSPSS	Nipple	76mm	76mm	152mm	1.27mm
CT66PSPSS	Nipple	152mm	152mm	152mm	1.27mm
CTS66PSPSS	Nipple	152mm	152mm	152mm	1.27mm
CT33SPSS	Nipple	76mm	76mm	152mm	1.27mm
CT46SPSS	Nipple	102mm	152mm	152mm	1.27mm
CTS66SPSS	Nipple	152mm	152mm	152mm	1.27mm
CTS44SPSS	Nipple	102mm	102mm	152mm	1.27mm
CTS44PSPSS	Nipple	102mm	102mm	152mm	1.27mm
CT44PSPSS	Nipple	102mm	102mm	152mm	1.27mm
CT46PSPSS	Nipple	102mm	152mm	152mm	1.27mm
CTS46SPSS	Nipple	102mm	152mm	152mm	1.27mm
CT44SPSS	Nipple	102mm	102mm	152mm	1.27mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE