



**Guida orizzontale, anteriore, tipo H-LD, pesante,
labbro lungo, per applicazione IEEE, 1000 mm**

CODICE A CATALOGO

34560-301



Combinations of horizontal rails and side panels

	$\Delta P = 0$ can be combined		$\Delta P = 1$ combinations not recommended	
RAILWAY 18		-	-	RAILWAY 18 supports
RAILWAY 22		+	to RAILWAY 18: double to RAILWAY 18: not recommended	RAILWAY 22 supports and RAILWAY 22 supports
RAILWAY 25		+	RAILWAY 25 double	+
RAILWAY 28		+	RAILWAY 28 double	-
RAILWAY 30		+	RAILWAY 30 double	-
RAILWAY 35		+	RAILWAY 35 double	-
RAILWAY 40		+	RAILWAY 40 double	-
RAILWAY 45		+	RAILWAY 45 double	-
RAILWAY 50		+	RAILWAY 50 double	-
RAILWAY 55		+	RAILWAY 55 double	-
RAILWAY 60		+	RAILWAY 60 double	-
RAILWAY 65		+	RAILWAY 65 double	-
RAILWAY 70		+	RAILWAY 70 double	-
RAILWAY 75		+	RAILWAY 75 double	-
RAILWAY 80		+	RAILWAY 80 double	-
RAILWAY 85		+	RAILWAY 85 double	-
RAILWAY 90		+	RAILWAY 90 double	-
RAILWAY 95		+	RAILWAY 95 double	-
RAILWAY 100		+	RAILWAY 100 double	-
RAILWAY 105		+	RAILWAY 105 double	-
RAILWAY 110		+	RAILWAY 110 double	-
RAILWAY 115		+	RAILWAY 115 double	-
RAILWAY 120		+	RAILWAY 120 double	-
RAILWAY 125		+	RAILWAY 125 double	-
RAILWAY 130		+	RAILWAY 130 double	-
RAILWAY 135		+	RAILWAY 135 double	-
RAILWAY 140		+	RAILWAY 140 double	-
RAILWAY 145		+	RAILWAY 145 double	-
RAILWAY 150		+	RAILWAY 150 double	-
RAILWAY 155		+	RAILWAY 155 double	-
RAILWAY 160		+	RAILWAY 160 double	-
RAILWAY 165		+	RAILWAY 165 double	-
RAILWAY 170		+	RAILWAY 170 double	-
RAILWAY 175		+	RAILWAY 175 double	-
RAILWAY 180		+	RAILWAY 180 double	-
RAILWAY 185		+	RAILWAY 185 double	-
RAILWAY 190		+	RAILWAY 190 double	-
RAILWAY 195		+	RAILWAY 195 double	-
RAILWAY 200		+	RAILWAY 200 double	-
RAILWAY 205		+	RAILWAY 205 double	-
RAILWAY 210		+	RAILWAY 210 double	-
RAILWAY 215		+	RAILWAY 215 double	-
RAILWAY 220		+	RAILWAY 220 double	-
RAILWAY 225		+	RAILWAY 225 double	-
RAILWAY 230		+	RAILWAY 230 double	-
RAILWAY 235		+	RAILWAY 235 double	-
RAILWAY 240		+	RAILWAY 240 double	-

La guida orizzontale con labbro lungo consente l'uso di maniglie di inserimento/estrazione IEEE.

CERTIFICAZIONI



CARATTERISTICHE

Per unità plug-in con impugnatura IEEE

Labbro lungo (H-LD)

Installazione in alto e in basso

Per sistemi CPCI e VME64x

Alluminio estruso, finitura anodizzata, superficie di contatto conduttiva

ATTRIBUTI DEL PRODOTTO

Larghezza rack: 195HP

Quantità nella confezione: 1

Finitura: Anodizzato

Lunghezza: 1000mm

Materiale: Alluminio

Famiglia di prodotti: EuropacPRO; RatiopacPRO; RatiopacPRO air; CompacPRO; PropacPRO

Tipo di prodotto: Guida orizzontale

Tipo: Per impieghi pesanti, LD

Funziona con: Rack secondari; Custodie

Net Weight: 0.389kg

INFORMAZIONI DI PRODOTTO AGGIUNTIVE

La consegna è in confezioni multiple standard. I prezzi si riferiscono a ciascun articolo.

Tenere presente che le consegne possono essere effettuate nei QSP indicati (ad esempio 5 pezzi, 10 pezzi, 50 pezzi, ecc.). Le quantità d'ordine diverse (ad esempio 2 pezzi) possono essere modificate con la quantità di consegna successiva possibile = quantità confezione standard.

AVVERTIMENTO

I prodotti nVent devono essere installati e utilizzati solo come indicato nelle schede istruzioni e nei materiali di formazione di nVent. Le schede istruzioni sono disponibili su www.nvent.com e presso il vostro rappresentante del servizio clienti nVent. Un'installazione scorretta, un uso improprio, un'applicazione errata o qualsiasi altro mancato rispetto completo delle istruzioni e degli avvertimenti di nVent può causare malfunzionamenti del prodotto, danni alla proprietà, gravi lesioni personali e morte e/o annullare la vostra garanzia.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Il nostro straordinario portafoglio di marchi:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE