

# Sistemi di spurgo e pressurizzazione

Purge and Pressurization is a protection method used with Type 4, 4X and 12 (IP54 recommended minimum) enclosures. The enclosure is initially purged to remove any internal explosive gases or dust. Once this is accomplished, the enclosure is pressurized with a protective air or inert gas supply. This provides a positive internal enclosure pressure which keeps any external explosive gases or dust from entering the enclosure. The two methods of purge and pressurization offered are Leak Compensation and Continuous Flow.

Leak Compensation maintains positive pressure by compensating for losses. System consists of Control Unit and Relief Valve. Certification Type Y and Z models: • Flush (internal) or external mount models • Local visual alarm indicator and dry contact output for remote alarm • Typically recommended for enclosures with volume of 60 Ft<sup>3</sup> or less. Certification Type X Model: • Provides power disconnect when pressurization is lost or not attained • Provides automatic purge process • External mount • Local visual alarm indicator and dry contact output for remote alarm • Typically recommended for enclosures with volume of 60 Ft<sup>3</sup> or less.

Continuous Flow provides positive pressure via continuous protective air flow through the enclosure. System consists of Control Unit, Calibrated Outlet Orifice and Relief Valve. Certification Type Y and Z Models: • Flush (internal) or external mount models • Local visual alarm indicator and dry contact output for remote alarm • Typically recommended for enclosures with volume of 17 Ft<sup>3</sup> or less



## STANDARD INDUSTRIALI

Type X

Ex [px] Ex [p]

IECEX SIR.0019X [Gb, Db]

Europe, ATEX Category 2 GD

Cert no Sira 14ATEX1045X

USA/Canada NFPA496 CI I Div 1 Groups A, B, C & D

UL E466718

Type Y

Ex [py] Ex [p]

IECEX SIR.0019X [Gb, Db]

Europe, ATEX Category 2 GD

Cert no Sira 14ATEX1045X  
North America CI I Div 1 Groups A, B, C & D  
For protecting CI I Div 2 equipment  
UL E466718  
Type Z  
Ex [pz] Ex [p]  
IECEX SIR.0019X [Gc, Dc]  
Europe, ATEX Category 3 GD  
Cert no Sira 14ATEX1045X  
North America CI I Div 2 Groups A, B, C & D  
UL E466718

## CARATTERISTICHE

---

All exterior components are 316 stainless steel or corrosion-resistant composite

Space-saving flush or exterior mounted models available

Local visual indicators provide system status

Leak compensation models are equipped with rapid purge valve and visual purge status indicator

All models utilize dry, clean inert gas supply of 60 PSI (4 bar) to 115 PSI (8 bar)

Ambient operating temperature -4°F (-20°C) to 131°F (55°C)

Type X models provide automatic purge cycle and 4PNO/20A/440VAC power contactor with 115 VAC or 230 VAC coil

## SPECIFICHE

**Finitura:** Spazzolato

**Materiale:** Acciaio inossidabile 316L

Table 1/1

Codice a catalogo	Spessore	Tipo di operazione	Montaggio	Dettagli della certificazione
PCFB1YZ	3.18mm	Flusso continuo	Esterno	Tipo Y, Tipo Z
PLCS1X2	3.18mm	Compensazione delle perdite	Esterno	Digitare X.
PLCS1X1	3.18mm	Compensazione delle perdite	Esterno	Digitare X.
PLCB1YZ	3.18mm	Compensazione delle perdite	Esterno	
PCFF1YZ	3.18mm	Flusso continuo	A filo	Tipo Y, Tipo Z
PLCF1YZ	3.18mm	Compensazione delle perdite	A filo	Tipo Y, Tipo Z
PLCSKIT				
PCFSKIT				

## INFORMAZIONI DI PRODOTTO AGGIUNTIVE

For all IEC and ATEC applications, the final or complete integrated assembly must be submitted to a notified body for certification.

See Specification Sheet for Purge and Pressurization Systems and Certifications table.

## AVVERTIMENTO

I prodotti nVent devono essere installati e utilizzati solo come indicato nelle schede istruzioni e nei materiali di formazione di nVent. Le schede istruzioni sono disponibili su [www.nvent.com](http://www.nvent.com) e presso il vostro rappresentante del servizio clienti nVent. Un'installazione scorretta, un uso improprio, un'applicazione errata o qualsiasi altro mancato rispetto completo delle istruzioni e degli avvertimenti di nVent può causare malfunzionamenti del prodotto, danni alla proprietà, gravi lesioni personali e morte e/o annullare la vostra garanzia.



Il nostro straordinario portafoglio di marchi:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**