



Horizontale rail voor, type H-KD, zwaar, korte lip, 1000 mm

CATALOGUSNUMMER

34560-201



Combinations of horizontal rails and side panels

		"4" can be combined.		"2" combination not recommended	
Product 1	Product 2	-	+	+	+
Product 1	Product 3	+	+	+	+
Product 1	Product 4	+	+	-	-
Product 1	Product 5	+	+	-	-
Product 1	Product 6	+	+	-	-
Product 1	Product 7	+	+	-	-
Product 1	Product 8	+	+	-	-
Product 1	Product 9	+	+	-	-
Product 1	Product 10	+	+	-	-
Product 1	Product 11	+	+	-	-
Product 1	Product 12	+	+	-	-
Product 1	Product 13	+	+	-	-
Product 1	Product 14	+	+	-	-
Product 1	Product 15	+	+	-	-
Product 1	Product 16	+	+	-	-
Product 1	Product 17	+	+	-	-
Product 1	Product 18	+	+	-	-
Product 1	Product 19	+	+	-	-
Product 1	Product 20	+	+	-	-
Product 1	Product 21	+	+	-	-
Product 1	Product 22	+	+	-	-
Product 1	Product 23	+	+	-	-
Product 1	Product 24	+	+	-	-
Product 1	Product 25	+	+	-	-
Product 1	Product 26	+	+	-	-
Product 1	Product 27	+	+	-	-
Product 1	Product 28	+	+	-	-
Product 1	Product 29	+	+	-	-
Product 1	Product 30	+	+	-	-
Product 1	Product 31	+	+	-	-
Product 1	Product 32	+	+	-	-
Product 1	Product 33	+	+	-	-
Product 1	Product 34	+	+	-	-
Product 1	Product 35	+	+	-	-
Product 1	Product 36	+	+	-	-
Product 1	Product 37	+	+	-	-
Product 1	Product 38	+	+	-	-
Product 1	Product 39	+	+	-	-
Product 1	Product 40	+	+	-	-
Product 1	Product 41	+	+	-	-
Product 1	Product 42	+	+	-	-
Product 1	Product 43	+	+	-	-
Product 1	Product 44	+	+	-	-
Product 1	Product 45	+	+	-	-
Product 1	Product 46	+	+	-	-
Product 1	Product 47	+	+	-	-
Product 1	Product 48	+	+	-	-
Product 1	Product 49	+	+	-	-
Product 1	Product 50	+	+	-	-

Aluminium extrusie horizontale rail van het type H-KD (H-KD = Heavy, Short Lip) met een geanodiseerd oppervlak en een geleidend contactoppervlak. Gedrukte HP markeringen voor een snelle optische positionering van de geleiderails. Geschikt voor RatiopacPRO/-AIR en EuropacPRO/-rugged).

CERTIFICERINGEN



KENMERKEN

Installatie aan de boven- en onderkant

Korte lip (H-KD)

Aluminium extrusie, geanodiseerde afwerking, geleidend contactoppervlak

PRODUCTKENMERKEN

Rekbreedte: 195HP

Hoeveelheid in verpakking: 1

Afwerking: Geanodiseerd

Lengte: 1000mm

Materiaal: Aluminium

Productserie: EuropacPRO; RatiopacPRO; RatiopacPRO air; CompacPRO; PropacPRO

Producttype: Horizontale rail

Type: Zwaar, KD

Werkt met: Subtracks; Omkastingen

Net Weight: 0.38kg

AANVULLENDE PRODUCTGEGEVENS

Levering vindt plaats in veelvouden van standaardverpakkingen. De prijs is per afzonderlijk item.

Houd er rekening mee dat leveringen kunnen worden uitgevoerd in de vermelde SPQ's (SPQ, bijv. 5 stuks, 10 stuks, 50 stuks, enz.). Afwijkende bestelhoeveelheden (bijv. 2 stuks) kunnen worden gewijzigd in de volgende mogelijke leveringshoeveelheid = Standard Pack Quantity.

WAARSCHUWING

nVent-producten moeten alleen worden geïnstalleerd en gebruikt zoals aangegeven in de instructiebladen en trainingsmateriaal van nVent. Instructiebladen zijn beschikbaar op www.nvent.com en bij uw nVent klantenservicevertegenwoordiger. Onjuiste installatie, misbruik, verkeerde toepassing of ander falen om de instructies en waarschuwingen van nVent volledig te volgen, kan leiden tot productstoringen, schade aan eigendommen, ernstig lichamelijk letsel en de dood en/of uw garantie ongeldig maken.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Ons krachtige merkenportfolio:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE