


Horizontal Rail, Front, Type R-LD, Rugged, Long Lip , 40 HP

NÚMERO DE CATÁLOGO

34566-340



Combinations of horizontal rails and side panels

$\oplus$ = can be combined, $\oplus^*$ = combination not recommended

RAILTYPE	RAILTYPE	RAILTYPE	RAILTYPE	RAILTYPE	RAILTYPE
RAILTYPE 1		-		RAILTYPE 2 required	
RAILTYPE 2		+	RAILTYPE 1 (Profile 1) required	RAILTYPE 2 (Profile 2) required	+
RAILTYPE 3		RAILTYPE 3 (Profile 3) required	RAILTYPE 3 (Profile 3) required	-	-
RAILTYPE 4		-	-	-	-
RAILTYPE 5		-	-	-	-
RAILTYPE 6		-	-	-	-
RAILTYPE 7		-	-	-	-
RAILTYPE 8		-	-	-	-
RAILTYPE 9		-	-	-	-
RAILTYPE 10		-	-	-	-

RAILTYPE 1: 100x100x10
 RAILTYPE 2: 100x100x10
 RAILTYPE 3: 100x100x10
 RAILTYPE 4: 100x100x10
 RAILTYPE 5: 100x100x10
 RAILTYPE 6: 100x100x10
 RAILTYPE 7: 100x100x10
 RAILTYPE 8: 100x100x10
 RAILTYPE 9: 100x100x10
 RAILTYPE 10: 100x100x10

The rugged horizontal rail type can handle shock and vibration up to 25 g. It enables the use of IEEE handles.

CERTIFICATIONS



CARACTERÍSTICAS

Type R-LD "rugged" horizontal rails with 3-hole fixing for increased robustness

For insertion/extraction of CompactPCI or, VME64x boards

With HP units printed from 28 HP upwards

Length 20, 28, 40, 42, 63, 84 HP or 1000 mm

Aluminum extrusion, anodized finish, conductive contact surface, with HP markings

CARACTERÍSTICAS DO PRODUTO

Rack Width: 40HP

Quantidade por embalagem: 1

Acabamento: Anodized

Length: 208.28mm

Material: Alumínio

Família de produtos: EuropacPRO

Product Type: Horizontal Rail

Tipo: Rugged, LD

Works With: Subracks

Gross Weight: 0.131kg

AVISO

Os produtos nVent devem ser instalados e utilizados apenas conforme indicado nas fichas de instrução do produto e materiais de treinamento da nVent. As fichas de instrução estão disponíveis em www.nVent.com e com nossos representantes de atendimento ao cliente nVent. A instalação inadequada, uso incorreto, aplicação incorreta ou outra falha qualquer em seguir completamente as instruções e avisos da nVent podem levar ao mau funcionamento do produto, danos à propriedade, lesões corporais graves e morte, e/ou anular sua garantia.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



O nosso forte portfólio de marcas:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE