


Outdoor Modular VENT Cabinet With Single Door, Fan, 1530H 29 U, 700W 730D

Data Solutions

NÚMERO DE CATÁLOGO

10149-334



Telecom and Railway applications require sophisticated electronics in outdoor setups. nVent SCHROFF Outdoor cabinets shield such electronic components from extreme weather and vandalism, ensuring operational continuity. Modular construction allows multiple configurations in size and function along with multiple cooling options.

CERTIFICATIONS



CARACTERISTICAS

Aluminium profile frame with removable, double-walled cladding

IP 55 or NEMA 12~

Double-walled

Extensive range of 19" cabinet accessories

Access to cabinet from front, all sides possible upon request

100 mm high plinth, 200 and 300 mm possible

Top cover with louvers, can be upgraded with fans or A/C unit

RAL 7035 powder coating, other colors available upon request

CARACTERÍSTICAS DO PRODUTO

Product Type: Outdoor Cabinet

Família de produtos: Modular

Rack Height: 29U

Altura: 1530mm

Largura: 700mm

Profundidade: 730mm

Wall Type: Double Walled

Door Type: Plain; Single Door

Access: Front

Burglar Resistance: Não

Cooling: Fan Ventilation

EMC Shielding: Não

Em conformidade com: IEC 61969-1; IEC 61969-2; IEC 61969-3; IEC 60917-1; IEC 60917-2; ETS 300119; IEC 60529; DIN EN 50178; VDE 0160; ETSI EN 300019-1-4

Cladding Color Code: RAL 7035

Grau de proteção: IP55

Battery Compartment: Sim

Cor: Light Gray

Código de cor: RAL 7035

Fan Quantity: 2

Acabamento: Pintura electrostática com Acabamento Texturado

Frame Material: Alumínio

Material: Alumínio; Aço

Mounting Setup: 19" Uprights

Quantidade por embalagem: 1

Plinth Height: 200mm

DETALHES ADICIONAIS DO PRODUTO

Height dimensions are without base/plinth.

AVISO

Os produtos nVent devem ser instalados e utilizados apenas conforme indicado nas fichas de instrução do produto e materiais de treinamento da nVent. As fichas de instrução estão disponíveis em www.nVent.com e com nossos representantes de atendimento ao cliente nVent. A instalação inadequada, uso incorreto, aplicação incorreta ou outra falha qualquer em seguir completamente as instruções e avisos da nVent podem levar ao mau funcionamento do produto, danos à propriedade, lesões corporais graves e morte, e/ou anular sua garantia.



O nosso forte portfólio de marcas:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE