

Kits de janelas para locais perigosos, EXWK

Hazardous Location Window Kits are designed to be used on Increased Safety (Ex e) enclosures in ATEX or IECEx Zone 1 or 2 hazardous areas. These window kits ensure a dust-, oil-, and water-tight seal. Designed for use as viewing windows, these window kits are ideal for visibility of internal enclosure components. The windows are easily installed by making a cutout in the enclosure and attaching the window and frame with included mounting hardware.

NORMAS DA INDÚSTRIA

UL 508A Component Recognized; Type 4, 4X,12, 3R; File No. E61997

IECEx and ATEX Approvals

Suitable for use on increased safety enclosures for ZONE 1 or ZONE 2 assemblies

ATEX Directive 94/9/EC

ATEX

Sira 13ATEX3315U

Ex e IIC Gb

Ex tb IIIC Db IP 66

IECEx

IECEx SIR 13.0123U

Ex e IIC Gb

Ex tb IIIC Db IP 66

cUR Component Recognized per CSA C22.2 No. 94; Type 4, 4X, 12,

3R; File No. E61997

NEMA/EEMAC 4, 4X, 12, 13

IEC 60529, IP66



CARACTERÍSTICAS

Secure sealing with silicon gasket to protect against water and dust ingress in high-temperature applications

Maintain visual on components through .25-in. (6-mm) tempered safety glass

Easy installation in enclosure cutouts with window frame hardware

ESPECIFICAÇÕES

Acabamento: Polido
Material: Aço Inoxidável 316L

Table 1/1

Número de catálogo	Espessura	Cutout Size
EXWK715SS6	1.98mm	424 x 221mm
EXWK53SS6	1.98mm	170 x 119mm
EXWK711SS6	1.98mm	221 x 322mm
EXWK95SS6	1.98mm	272 x 183mm
EXWK720SS6	1.98mm	221 x 551mm
EXWK1711SS6	1.98mm	475 x 322mm
EXWK138SS6	1.98mm	373 x 246mm
EXWK2919SS6	1.98mm	780 x 526mm
EXWK724SS6	1.98mm	221 x 653mm
EXWK2315SS6	1.98mm	627 x 424mm
EXWK729SS6	1.98mm	221 x 780mm

AVISO

Os produtos nVent devem ser instalados e utilizados apenas conforme indicado nas fichas de instrução do produto e materiais de treinamento da nVent. As fichas de instrução estão disponíveis em www.nVent.com e com nossos representantes de atendimento ao cliente nVent. A instalação inadequada, uso incorreto, aplicação incorreta ou outra falha qualquer em seguir completamente as instruções e avisos da nVent podem levar ao mau funcionamento do produto, danos à propriedade, lesões corporais graves e morte, e/ou anular sua garantia.



O nosso forte portefólio de marcas:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE