

Strut Seismic Hinge



CARACTERISTICI

Complete hinge assembly

Ideal for attaching sway bracing to MEP system supports

Attaches to strut trapezes and to structure

SPECIFICAȚII

Finish: Electrogalvanized

Material: Oțel

Table 1/1

Număr de catalog	Article Number	Hole Size 1 (HS1)	Hole Size 2 (HS2)	Length (L)	Width (W)	Thickness (T)
CSBSH00625E G	404465	14 mm	17 mm	179.8mm	41.3 mm	6.4 mm
CSBSH00375E G	404463	14 mm	11 mm	179.8mm	41.3 mm	6.4 mm
CSBSH00500E G	404464	14 mm	14 mm	179.8mm	41.3 mm	6.4 mm
CSBSH00750E G	404466	14 mm	21 mm	179.8mm	41.3 mm	6.4 mm

DIAGRAMS



AVERTIZARE

Produsele nVent trebuie instalate și utilizate numai așa cum este indicat în fișele de instrucțiuni și materialele de formare ale nVent. Fișele de instrucțiuni sunt disponibile pe www.nvent.com și de la reprezentantul dvs. de servicii clienți nVent. O instalare incorectă, o utilizare abuzivă, o aplicare greșită sau orice altă lipsă de respectare completă a instrucțiunilor și avertismentelor nVent poate duce la defectarea produsului, la deteriorarea proprietății, la răniri corporale grave și moarte și/sau poate anula garanția dvs.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Portofoliul nostru puternic de mărci:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE

