

PropacPRO Desktop Case, Unshielded



The nVent SCHROFF PropacPRO case provides electronics protection for 19" and individual electronic assemblies. The aluminum die cast frames and profile sidepanels guarantee a robust solution. In addition an extensive accessory range is available.

CERTIFICATIONS



CARACTERISTICI

Desktop case for individual assembly

Ventilation slots in base plate

Retrofitable EMC shielding

Prepared for GND/earthing

Conforms with DIN EN 62368-1

SPECIFICAȚII

- Product Type:** Case
- Type:** Case for Individual Electronic Components
- Product Family:** PropacPRO

Table 1/2

Număr de catalog	Rack Height	Rack Width	Depth	Package Quantity	Usable Height	Usable Width
14576-465	6U	84HP	386mm	1	262.8mm	432mm
14576-241	4U	63HP	266mm	1	174mm	326mm

Număr de catalog	Rack Height	Rack Width	Depth	Package Quantity	Usable Height	Usable Width
14576-169	3U	84HP	506mm	1	130mm	432mm
14576-463	6U	84HP	326mm	1	262.8mm	432mm
14576-467	6U	84HP	446mm	1	262.8mm	432mm
14576-143	3U	63HP	326mm	1	130mm	326mm
14576-123	3U	42HP	326mm	1	130mm	219mm
14576-043	2U	63HP	326mm	1	85.1mm	326mm
14576-167	3U	84HP	446mm	1	130mm	432mm
14576-023	2U	42HP	326mm	1	85.1mm	219mm
14576-125	3U	42HP	386mm	1	130mm	219mm
14576-243	4U	63HP	326mm	1	174mm	326mm
14576-223	4U	42HP	326mm	1	174mm	219mm
14576-121	3U	42HP	266mm	1	130mm	219mm
14576-145	3U	63HP	386mm	1	130mm	326mm
14576-269	4U	84HP	506mm	1	174mm	432mm
14576-041	2U	63HP	266mm	1	85.1mm	326mm
14576-245	4U	63HP	386mm	1	174mm	326mm
14576-165	3U	84HP	386mm	1	130mm	432mm
14576-045	2U	63HP	386mm	1	85.1mm	326mm

Table 2/2

Număr de catalog	Rack Height	Rack Width	Depth	Package Quantity	Usable Height	Usable Width
14576-469	6U	84HP	506mm	1	262.8mm	432mm
14576-247	4U	63HP	446mm	1	174mm	326mm
14576-103	3U	28HP	326mm	1	130mm	148mm
14576-221	4U	42HP	266mm	1	174mm	219mm
14576-267	4U	84HP	446mm	1	174mm	432mm
14576-141	3U	63HP	266mm	1	130mm	326mm
14576-161	3U	84HP	266mm	1	130mm	432mm
14576-163	3U	84HP	326mm	1	130mm	432mm
14576-021	2U	42HP	266mm	1	85.1mm	219mm
14576-265	4U	84HP	386mm	1	174mm	432mm
14576-101	3U	28HP	266mm	1	130mm	148mm

Table 1/2

Număr de catalog	Front Frame Construction	Cooling Option	Complies With	EMC Shielding	Finish	Height
14576-465	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	289mm
14576-241	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-169	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-463	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	289mm
14576-467	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	289mm
14576-143	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-123	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-043	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	111mm
14576-167	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-023	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	111mm
14576-125	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-243	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-223	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-121	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-145	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-269	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-041	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	111mm
14576-245	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-165	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm

Număr de catalog	Front Frame Construction	Cooling Option	Complies With	EMC Shielding	Finish	Height
14576-045	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	111mm

Table 2/2

Număr de catalog	Front Frame Construction	Cooling Option	Complies With	EMC Shielding	Finish	Height
14576-469	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	289mm
14576-247	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-103	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-221	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-267	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-141	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-161	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-163	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm
14576-021	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	111mm
14576-265	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	200mm
14576-101	Single Piece	No	IEC 60297-3-101	No (Retrofittable)	Passivated, Vopsit Pulbere	155.5mm

Table 1/2

Număr de catalog	Material	Protection Rating	Static Load	Width
14576-465	Aluminiu	IP20	25kg	470.3mm
14576-241	Aluminiu	IP20	25kg	363.7mm
14576-169	Aluminiu	IP20	25kg	470.3mm
14576-463	Aluminiu	IP20	25kg	470.3mm
14576-467	Aluminiu	IP20	25kg	470.3mm
14576-143	Aluminiu	IP20	25kg	363.7mm
14576-123	Aluminiu	IP20	25kg	257mm
14576-043	Aluminiu	IP20	25kg	363.7mm

Număr de catalog	Material	Protection Rating	Static Load	Width
14576-167	Aluminiu	IP20	25kg	470.3mm
14576-023	Aluminiu	IP20	25kg	257mm
14576-125	Aluminiu	IP20	25kg	257mm
14576-243	Aluminiu	IP20	25kg	363.7mm
14576-223	Aluminiu	IP20	25kg	257mm
14576-121	Aluminiu	IP20	25kg	257mm
14576-145	Aluminiu	IP20	25kg	363.7mm
14576-269	Aluminiu	IP20	25kg	470.3mm
14576-041	Aluminiu	IP20	25kg	363.7mm
14576-245	Aluminiu	IP20	25kg	363.7mm
14576-165	Aluminiu	IP20	25kg	470.3mm
14576-045	Aluminiu	IP20	25kg	363.7mm

Table 2/2

Număr de catalog	Material	Protection Rating	Static Load	Width
14576-469	Aluminiu	IP20	25kg	470.3mm
14576-247	Aluminiu	IP20	25kg	363.7mm
14576-103	Aluminiu	IP20	25kg	185.9mm
14576-221	Aluminiu	IP20	25kg	257mm
14576-267	Aluminiu	IP20	25kg	470.3mm
14576-141	Aluminiu	IP20	25kg	363.7mm
14576-161	Aluminiu	IP20	25kg	470.3mm
14576-163	Aluminiu	IP20	25kg	470.3mm
14576-021	Aluminiu	IP20	25kg	257mm
14576-265	Aluminiu	IP20	25kg	470.3mm
14576-101	Aluminiu	IP20	25kg	185.9mm

DETALII SUPLIMENTARE DESPRE PRODUS

Case, 2 U with side panel for tip-up carrying handle on request.

AVERTIZARE

Produsele nVent trebuie instalate și utilizate numai așa cum este indicat în fișele de instrucțiuni și materialele de formare ale nVent. Fișele de instrucțiuni sunt disponibile pe www.nvent.com și de la reprezentantul dvs. de servicii clienți nVent. O instalare incorectă, o utilizare abuzivă, o aplicare greșită sau orice altă lipsă de respectare completă a instrucțiunilor și avertismentelor nVent poate duce la defectarea produsului, la deteriorarea proprietății, la răniri corporale grave și moarte și/sau poate anula garanția dvs.

North America

All locations

+1.763.422.2661

Chat with us:

nvent.com/schroff

Europe

Straubenhardt, Germany

+49.7082.794.0

Betschdorf, France

+33.3.88.90.64.90

Warsaw, Poland

+48.22.209.98.35

Assago, Italy

+39.02.932.7141

Chat with us:

nvent.com/schroff

Asia

Shanghai, China

+86.21.2412.6943

Qingdao, China

+86.532.8771.6101

Singapore

+65.6768.5800

Shin-Yokohama, Japan

+81.45.476.0271

Chat with us:

nvent.com/schroff

Middle East & India

Dubai, United Arab

Emirates

+971.4.378.1700

Bangalore, India

+91.80.6715.2001

Istanbul, Turkey

+90.216.250.7374

Chat with us:

nvent.com/schroff



Portofoliul nostru puternic de mărci:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE