



MCD

The mild steel double door combinable floor standing enclosure range, MCD, is ideal for installation in confined spaces where a single door, when opened, would take up too much space in front of the enclosure. The doors' loading capacity also increases as it is divided over two doors. With a IP 55 protection degree, components inside the enclosure are well protected and makes it well suited for many different applications.



????

cUL ????? CSA C22.2 No.0?No.0.4?No.14?No.94; Type 12; ???
E92044

cUL Listed per CSA C22.2 No.0, No.0.4, No.14, No.94; Type 12;
File No. E92044

UL?DNV?CE?EAC

CSA, File No. 1442951: Type 12

IEC 62208 IP55

CE, UK CA, UL, DNV

??

Levering inkluderer: Ramme med monterede døre, bagpanel, toppanel, bundplader, monteringsplade og dørramme (ikke inkluderet i PER5-version). For skabe 2200 mm høje, inkluderer leveringen to stk CMB-profiler monteret i dybde. Levering omfatter også bolte til jording. Leveres på en palle i samme bredde som skabet, så skabet kan klargøres uden at fjerne det fra pallerne. Emballage kan genbruges.}

Material: Frame: 1.5 mm painted steel. Doors: 2 mm painted steel. Rear, roof and side panels: 1.5 mm painted steel. Mounting plate: 3 mm galvanized steel. Bottom plates: 1 mm galvanized steel.

Frame: Seam welded reversed open profiles with 25 mm hole pattern, according to DIN 43660. Including integrated external hole pattern.

Doors: Mounted with four hinges. Including door frame with 25 mm hole pattern. Doors cannot be reversed. Separate doors to be ordered for left hand door locking.

Rear panel: Fitted by M6 torx screws. Standard facilities for rear doors mounting. Split rear panels in 1600 mm wide enclosures. RD version comes with rear door instead of rear panel.

Side panels: Supplied as an accessory.

Roof panel: Removable.

Lock: Espagnolette 4-point locking system in the main door and 2-point locking system in the secondary door. Standard double-bit lock with 3 mm insert. Standard inserts, cylinders, lift handles and T-handles are available as accessories.

Bottom plates: Consists of three or four (D>600) pieces.

Mounting plate: Double folded and slides into position. Adjustable in depth by steps of 25 mm, with the MPD02 accessory. Supplied, attached on the outside of the enclosure packaging.

Earthing: All panels are earthed through their fittings and equipped with a separate earthing stud.

Finish: RAL 7035 structured powder coating.

Protection: Complies with IP55 | TYPE 12 | IK 10.

Mounting requirements: Standard delivery ready for combined installation. For stand-alone installation add side panels.

- : 1.5mm
- : 2mm
- : □□
- : □□
- : □□□□
- : RAL 7035

Table 1/2

□□□	□□□	□□ (H)	□□ (W)	□□ (D)	□□□□	□□□□
MCD18124R5	MCD18124R5	1800mm	1200mm	400mm	□	66.7mm
MCD20104R5	MCD20104R5	2000mm	1000mm	400mm	□	74.57mm
MCD18126PER5		1800mm	1200mm	600mm	□	
MCD22106R5	MCD22106R5	2200mm	1000mm	600mm	□	82.44mm
MCD20125R5	MCD20125R5	2000mm	1200mm	500mm	□	74.57mm
MCD20128PERDR5		2000mm	1200mm	800mm	□	
MCD18125R5	MCD18125R5	1800mm	1200mm	500mm	□	66.7mm
MCD22126PER5		2200mm	1200mm	600mm	□	
MCD18104PER5		1800mm	1000mm	400mm	□	
MCD18125PER5		1800mm	1200mm	500mm	□	
MCD20105R5	MCD20105R5	2000mm	1000mm	500mm	□	74.57mm
MCD20105PER5		2000mm	1000mm	500mm	□	
MCD22126R5	MCD22126R5	2200mm	1200mm	600mm	□	82.44mm
MCD20125PER5		2000mm	1200mm	500mm	□	
MCD20106PER5		2000mm	1000mm	600mm	□	
MCD18105R5	MCD18105R5	1800mm	1000mm	500mm	□	66.7mm
MCD20106R5	MCD20106R5	2000mm	1000mm	600mm	□	74.57mm
MCD20126PERDR5		2000mm	1200mm	600mm	□	
MCD20126RDR5		2000mm	1200mm	600mm	□	
MCD20124R5	MCD20124R5	2000mm	1200mm	400mm	□	74.57mm

Table 2/2

□□□	□□□	□□ (H)	□□ (W)	□□ (D)	□□□□	□□□□
-----	-----	--------	--------	--------	------	------



?????????:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE