


Guide Rail With Coding for CompactPCI/ VME64x, PC



New generation of With Coding type guide rails for PCBs or plug-in units. Forms a reliable interface between the subrack mechanics and the sub-assemblies. With the optimized design and the new high quality plastic material not just the stability was significantly increased, but also the fire safety properties improved. Which means the material ensures a low flammability, low smoke toxicity and density and fulfills the EN 45545-2 (Fire Safety in Railway Vehicle) requirements sets R22, R23 and R24 with the

??



??

????????????? PCB ??????????

???????, ?????????????? (PC)

????????, ?? EN 45545-2 ?? R22, R23 ? R24 ????????? HL3

“????”, ?? IEC 61249-2-21 ??

???????????????????? 1.5 mm???

?????????? H ?? R ?????????????????????

?? ESD ??? PCB ??????????????

?????? -40 °C.. 130 °C

????

□□ : □□ ; □□□ ; 19" □□ ; □□

□□ : □□

□□□□ : EuropacPRO; RatiopacPRO; RatiopacPRO AIR; CompacPRO; PropacPRO; MultipacPRO; Inpac

□□□□ : □□

Table 1/2

□□□	□□	□□	□□□□	□□□	□□	□□□□	□□
-----	----	----	------	-----	----	------	----


















64568-110		□□ , □□	1	160mm	2.5	EN 45545-2
64568-085		□□	1	70mm	2	EN 45545-2
64568-112		□□ , □□	1	220mm	2.5	EN 45545-2
64568-111		□□ , □□	1	220mm	2.5	EN 45545-2
64568-086		□□	1	70mm	2	EN 45545-2
64568-109		□□ , □□	1	160mm	2.5	EN 45545-2
64568-091		□□	1	220mm	2	EN 45545-2
64568-090		□□	1	160mm	2	EN 45545-2
64568-092		□□	1	220mm	2	EN 45545-2
64568-089		□□	1	160mm	2	EN 45545-2
24568-360		□□	10	70mm	2	EN 45545-2
24568-358		□□	10	160mm	2	EN 45545-2
24568-357		□□	10	70mm	2	EN 45545-2
24568-356		□□	10	160mm	2	EN 45545-2
24568-332		□□ , □□	10	340mm	2.5	EN 45545-2
24568-331		□□ , □□	10	280mm	2.5	EN 45545-2
24568-341		□□ , □□	10	280mm	2.5	EN 45545-2
24568-342		□□ , □□	10	340mm	2.5	EN 45545-2

Table 2/2

□□□	□□
64568-110	
64568-085	
64568-112	
64568-111	
64568-086	
64568-109	
64568-091	
64568-090	
64568-092	
64568-089	

